




# Balfit® Hydraulic Hose Fittings

## DOUBLE SKIVE Balfit® SAE 100R13 / SAE 100R15 / DIN 4SH

carbon steel ferrule for crimping on double-skived (internally and externally) high pressure **DIN EN 856 4SH**, **SAE 100R13** & **SAE 100R15** hydraulic hoses


**Material:** carbon steel, zinc plated

**Connectors:** Balfit® crimped fittings 26 serie



### 20.405 - Ferrule for DIN EN 856 4SH Hose (1.1/4", 1.1/2" and 2")

part number	hose dash	hose Ø		dimensions (mm)	
		mm	inch	L	D
20.405.20	- 20	31,8	1.1/4"	88	55
20.405.24	- 24	38,1	1.1/2"	94	62
20.405.32	- 32	50,8	2"	99	80



### 20.406 - Ferrule for DIN EN 856 4SH Hose (3/4" and 1"), SAE 100R13 Hose (all sizes) and SAE 100R15 Hose (all sizes)

part number	hose dash	hose Ø		dimensions (mm)	
		mm	inch	L	D
20.406.12	- 12	19,1	3/4"	60	38
20.406.16	- 16	25,4	1"	75	46
20.406.20	- 20	31,8	1.1/4"	88	60
20.406.24	- 24	38,1	1.1/2"	94	65
20.406.32	- 32	50,8	2"	99	80

also available:

### Balfit® Stainless Steel DOUBLE SKIVE Powerspir Ferrules

(add an 'S' at the end of the part number; ex: 20.405.20S or 20.406.12S)

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex® – The European Technology**