



Fig. 241
RACOR REDUCCIÓN LATÓN M/H
BUSHINGS BRASS M/F

INFORMACIÓN TÉCNICA - TECHNICAL INFORMATION

DN	COD.	DIMENSIONES - DIMENSIONS			Peso aprox. Weight aprox. (g)
		L (mm)	G (inches)	G1 (inches)	
1/4" x 1/8"	LRA0141418	10,0	1/4"	1/8"	5
3/8" x 1/8"	LRA0143818	13,0	3/8"	1/8"	13
3/8" x 1/4"	LRA0143814	13,0	3/8"	1/4"	10
1/2" x 1/4"	LRA0141214	14,5	1/2"	1/4"	25
1/2" x 3/8"	LRA0141238	14,5	1/2"	3/8"	15
3/4" x 3/8"	LRA0143438	15,0	3/4"	3/8"	35
3/4" x 1/2"	LRA0143412	16,0	3/4"	1/2"	27
1" x 1/2"	LRA0141112	17,5	1"	1/2"	63
1" x 3/4"	LRA014134	17,5	1"	3/4"	46
1 1/4" x 1/2"	LRA01411412	19,5	1 1/4"	1/2"	114
1 1/4" x 3/4"	LRA01411434	19,5	1 1/4"	3/4"	96
1 1/4" x 1"	LRA0141141	19,5	1 1/4"	1"	73
1 1/2" x 1/2"	LRA01411212	20,5	1 1/2"	1/2"	131
1 1/2" x 3/4"	LRA01411234	20,5	1 1/2"	3/4"	140
1 1/2" x 1"	LRA0141121	20,5	1 1/2"	1"	119
1 1/2" x 1 1/4"	LRA014112114	20,5	1 1/2"	1 1/4"	73
2" x 1/2"	LRA014212	25,5	2"	1/2"	235
2" x 3/4"	LRA014234	25,5	2"	3/4"	224
2" x 1"	LRA01421	25,5	2"	1"	217
2" x 1 1/4"	LRA0142114	25,5	2"	1 1/4"	215
2" x 1 1/2"	LRA0142112	25,5	2"	1 1/2"	168
2 1/2" x 1 1/4"	LRA014212114	28,0	2 1/2"	1 1/4"	346
2 1/2" x 1 1/2"	LRA014212112	28,0	2 1/2"	1 1/2"	329
2 1/2" x 2"	LRA0142122	28,0	2 1/2"	2"	310
3" x 2"	LRA01432	33,0	3"	2"	596
3" x 2 1/2"	LRA0143212	33,0	3"	2 1/2"	375
4" x 2"	LRA01442	44,0	4"	2"	930
4" x 2 1/2"	LRA0144212	44,0	4"	2 1/2"	898
4" x 3"	LRA01443	44,0	4"	3"	970



CARACTERÍSTICAS BÁSICAS

- Cuerpo en latón CW617N-DW según UNE-EN 12165.
- Método de fabricación: Forja en caliente.
- Rosca de unión según UNE-EN ISO 228-1.
- Accesorios conforme a la norma UNE-EN 1254-4.
- Rango de temperatura de trabajo: -20 a 130 °C.
- Presión máxima de ejercicio: PN 25.

APLICACIONES GENERALES

- Agua sanitaria fría y caliente.

INSTRUCCIONES DE MONTAJE

- Aplicar en la rosca teflón o sellante similar para obtener una mayor estanqueidad en la unión.
- Evitar el exceso del material añadido para prevenir posibles roturas por el excesivo apriete.
- Colocar el accesorio en la instalación, con atención de no exceder el apriete de la pieza.

Observaciones:

Dada la complejidad, variedad y gran cantidad de especificaciones particulares de cada instalación, en conjunción con la existencia de diversos factores que pueden afectar a las condiciones de trabajo y naturaleza del producto, es responsabilidad del usuario final realizar los ensayos necesarios para garantizar el correcto funcionamiento del producto en cada aplicación concreta.

La instalación del producto deberá realizarse y mantenerse siguiendo códigos de buena práctica y/o estándares existentes.

BASIC FEATURES

- Body in brass CW617N-DW according to EN 12165.
- Production method: Hot forging.
- Threads according to EN ISO 228-1.
- Fittings comply with EN 1254-4 standard.
- Working temperature range: -20 to 130 °C.
- Maximal working pressure: PN 25.

GENERAL APPLICATIONS

- Cold and hot sanitary water.

ASSEMBLING INSTRUCTIONS

- Place over the fitting PTFE or similar sealant in order to obtain a better tightness on the coupling.
- Avoid any surplus of sealant in order to prevent possible breakings caused by excessive clamping.
- Connect the fitting with the installation. Pay attention to not exceeding in fitting clamping.

Remarks:

Due to the complexity, variety and large number of particular specifications for each installation, along with the existence of diverse factors which can affect the working conditions and nature of the product, it is the responsibility of the end-user to carry out the necessary tests to ensure the proper functioning of the product in any specific application.

Product installation must be carried out and maintained following the good practice codes and/or updated technical standards.

Nota : Debido al constante desarrollo de nuestros productos, los datos suministrados pueden ser alterados sin previo aviso.

Note : Due to the continuous development of our products, specifications may be changed without notification at any time.

Rev.2-04.20
2/2